

FLASH 06S SINGLE

DETECTOR IN HOUSING

is an detector with an **interference filter**. Detector can be adjusted using interference filter at one fixed wavelength in range of **200 – 600 nm**. Noise level at 254 nm is $\pm 2 \cdot 10^{-5}$ AU with a test cell. (Filter **254 nm include price**, other filters on request).

High standard **deuterium lamp** in a special socket enables **easy changing**.

This unit is used in liquid chromatography in **flash and preparative** applications. By using analytical cell can be detector used also for analytical purpose.

The unit is designed as stand alone with 90-264 V power supply and RS 232 controlling. It is



deriver from OEM build-in unit with powering 24-36 V DC.

The unit offers many advantages:

- **wavelength setting** from 200 up to 600 nm according used interference filter
- lamp **work hours** are counted using the built-in counter
- the **cell is easy to replace** from the side of the detector
- **powering by 90-264 V**
- **unit is controlled by RS232 interface**

SPECIFICATION

TECHNICAL PARAMETERS:

Wavelength range-according used interference filter	200 - 600 nm (standard installed filter 254 nm)
Typical spectral half-width	According used interference filter
Light source	Deuterium discharge lamp
Noise level at test cell (254 nm, TC 1.5 s)	$\pm 2 \times 10^{-5}$ AU
Drift at test cell (254 nm after 1 h)	1×10^{-3} AU/hr
Materials in contact with mobile phase	PTFE; fused silica, stainless steel
Time constant (T63)	0 s; 0.3 s; 0.6 s; 1.5 s
Output for integrator	1 V/AU (in digital form only)
Interface	RS232
Power supply	90-264 V
Power input	90 VA
Dimensions (W x H x D)	220 x 170 x 450 mm
Weight	7.9 kg

PREPARATIVE CELL PLCC 15 (SUPPLIED WITH UNIT)

volume/optical path (adjustable)	45 μ l / 0.3 mm (basic) 55 μ l / 1.4 mm 70 μ l / 2.4 mm
Cell connecting	tubing with OD = 1/8", thread 1/4"-28
Maximal flow rate	500 ml/min